

These day / night speed dome PTZ cameras have an awesome set of features and specifications. They allow you to pan, tilt, or zoom up to 100X (total zoom = optical zoom X digital zoom). Great choice with the Optiview DVRs.

Note: To use a PTZ camera on our PC-Based DVRs, you must have an RS485 Converter.

## Product Includes

- Ceiling bracket
- Power supply
- Installation / Instruction Manual
- Free technical support
- Wall bracket is optional

## **Features**

- 10X Samsung Digital Zoom
- 10X Optical Zoom
- 127 Presets
- 8 Programmable Group Tours
- On Screen Display (OSD)
- Vandal-Proof Armor Dome
- Indoor / Outdoor
- Day / Night
- Small Footprint

**Specifications** 

Image sensor: 1/4" Samsung CCD

Horizontal Resolution: 500 TV Lines (Color), 570 TV Lines (B/W)

Min. Illumination 0.7 Lux (Day/Color), 0.02 Lux (Night/B&W)

**Pan Speed:** 0-360° /s

Tilt Speed: 0-180° /s (Autoflip), 0-95° /s (Normal)

 Optical Zoom:
 10X

 Digital Zoom:
 10X

 Pixels:
 768 x 494

 SN Ratio:
 > 50db

Power: 12VDC 750ma (included)

Gain Control: Auto/Manual Back Light Compensation: Auto/Manual

**Lens:** 3.8 ~ 38mm, F1.8

Pan: 360 degrees continuous pan rotation

Preset Positions: 127

**Comm Port:** RS485 Pelco-D, Pelco-P selectable

Dimensions (mm):

Dome = 100.5mm (Diam)

Housing = 141mm (Diam) 140mm (Height)

Dimensions (inches): Dome = 3.96in (Diam)

Housing = 5.56in (Diam) 5.51in (Height)

Operating
Temperature:

OC ~ 40C (22F ~ 104F)

Weight: 1.5kg (about 3.5lbs)

Power Consumption: 9W Max